



Technical Data Sheet

SYL-OFF™ SD 7226 Dispersion

FEATURES & BENEFITS

- Low – Medium release force
- Good anchorage

Solvent-based silicone release coating

APPLICATIONS

- Release coating for pressure sensitive laminate/label stock.
- Single and double-sided industrial release papers or plastic films.
- Coatings for liners of technical adhesive tapes.

TYPICAL PROPERTIES

Specification Writers: These values are not intended for use in preparing specifications.

Property	Unit	Result
Physical form		Liquid
Appearance		Colorless
Viscosity at 25°C (77°F)	mPa.s	18000
Active ingredients	%	30
Diluent		Toluene
Flash Point, SETA closed cup	°C	5

DESCRIPTION

SYL-OFF™ SD 7226 Dispersion is a release coating component with 30% silicone solids in toluene.

**WWW.CONSUMER.DOW.COM,
OR FROM YOUR DOW SALES
APPLICATION ENGINEER, OR
DISTRIBUTOR, OR BY CALLING
DOW CUSTOMER SERVICE.**

HOW TO USE

Recommendations about how to use and formulate this product can be obtained from Dow.

USABLE LIFE AND STORAGE

When stored at or below 30°C in the original unopened containers, SYL-OFF SD 7226 Dispersion has a usable life of 6 months from the date of production.

HANDLING PRECAUTIONS

**PRODUCT SAFETY
INFORMATION REQUIRED FOR
SAFE USE IS NOT INCLUDED IN
THIS DOCUMENT. BEFORE
HANDLING, READ PRODUCT
AND SAFETY DATA SHEETS AND
CONTAINER LABELS FOR SAFE
USE, PHYSICAL AND HEALTH
HAZARD INFORMATION. THE
SAFETY DATA SHEET IS
AVAILABLE ON THE DOW
WEBSITE AT**

PACKAGING INFORMATION

SYL-OFF SD 7226 Dispersion is available in pail packaging of 17 kg.

LIMITATIONS

This product is neither tested nor represented as suitable for medical or pharmaceutical uses.

HEALTH AND ENVIRONMENTAL INFORMATION

To support customers in their product safety needs, Dow has an extensive Product Stewardship organization and a team of product safety and regulatory compliance specialists available in each area.

For further information, please see our website, www.consumer.dow.com or consult your local Dow representative.

LIMITED WARRANTY INFORMATION – PLEASE READ CAREFULLY

The information contained herein is offered in good faith and is believed to be accurate. However, because conditions and methods of use of our products are beyond our control, this information should not be used in substitution for customer's tests to ensure that our products are safe, effective, and fully satisfactory for the intended end use. Suggestions of use shall not be taken as inducements to infringe any patent.

Dow's sole warranty is that our products will meet the sales specifications in effect at the time of shipment.

Your exclusive remedy for breach of such warranty is limited to refund of purchase price or replacement of any product shown to be other than as warranted.

TO THE FULLEST EXTENT PERMITTED BY APPLICABLE LAW, DOW SPECIFICALLY DISCLAIMS ANY OTHER EXPRESS OR IMPLIED WARRANTY OF FITNESS FOR A PARTICULAR PURPOSE OR MERCHANTABILITY.

DOW DISCLAIMS LIABILITY FOR ANY INCIDENTAL OR CONSEQUENTIAL DAMAGES.

www.syloff.com



®Trademark of The Dow Chemical Company

UNRESTRICTED – May be shared with anyone

®™Trademark of The Dow Chemical Company ("Dow") or an affiliated company of Dow
SYL-OFF™ SD 7226 Dispersion

© 2017 The Dow Chemical Company. All rights reserved.

Form No. 30-1261-01 A